



Typical Chemical Characteristics

Product:

Anax 4006 “Fully Synthetic Ultra Low SAPS” SAE 5W-40 & 5W-30

Description:

EN:

Fully synthetic oil with **Ultra Low SAPS** technology for diesel or gasoline engines, equipped with **DPF** or **TWC** emission reduction catalysts. It protects the exhaust emission systems and also the engine protection for long drain performance.

EL:

Πλήρες συνθετικό λιπαντικό με τεχνολογία “**Ultra Low SAPS**”, για νέας γενιάς κινητήρες πετρελαίου ή βενζίνης με καταλύτες μείωσης ρύπων τύπου “**DPF** ή **TWC**”. Προστατεύει και προσφέρει μακροζωία στο σύστημα του καταλύτη και επίσης στον κινητήρα.

DE:

Vollsynthetisches Öl der **Ultra Low SAPS** Technologie für Diesel- oder Benzinmotoren, welche mit **DPF-** oder **TWC-**Katalysatoren zur Emissionsminderung ausgestattet sind. Schützt die Abgasanlage und den Motor für lange Ölwechselintervalle bei Topleistung.

RU:

Полностью синтетическое масло, изготовленное по технологии **Low SAPS** (пониженного содержания сульфатной зольности, фосфора и серы) и предназначенное для дизельных или бензиновых двигателей, оснащенных сажевыми фильтрами или трехкомпонентными катализаторами для сокращения уровня выбросов. Защищает системы выхлопных газов, а также обеспечивает защиту двигателя без необходимости частой замены.

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although RS200 motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and RS200 motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.



Typical Chemical Characteristics

Characteristics:

Property	Method	Unit	5W-40	5W-30
Specific Gravity 15°C	ASTM D 1298	kg/L	0,879	0,875
Viscosity at 100°C	ASTM D 445	cSt	12,5 - 16,3	9,3 - 12,5
Viscosity Index	-	-	>130	>130
Pour Point	ASTM D 97	°C	<-30	<-30
Flash Point	ASTM D 92	°C	>195	>192
Total Base Number	ASTM D 2896	mgKOH/g	>6,5	>6,5
Color	-	-	Crystal gold	Crystal gold
Cold Cranking Simulator	ASTM D 5293	mPa-s	<3500 @ -25°C	<3500 @ -25°C

Specifications:

ACEA: C4-12,
Mercedes Benz p226.51/p229.51
& Renault RNO720

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although RS200 motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and RS200 motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.