



Typical Chemical Characteristics

Product:

Axion IV HD SAE 50 & 40

Description:

EN:

Heavy Duty mineral mono-grade lubricant with Full SAPS technology that provides complete secure engine operation, even in condition of mechanical exhaustion, where heavy hauls or where extreme climatological conditions exist. Offers perfect engine's lubrication and endurance from oxidation and wear, while conserves the engine's mechanical parts clean from carbon deposits.

EL:

Ειδικά πρωτογενή μονότυπα λιπαντικά κατασκευασμένα με την τεχνολογία Full SAPS. Ωστε να παρέχει υψηλή προστασία στον κινητήρα, ακόμα και σε συνθήκες υψηλής καταπόνησης από βαρέα φορτία ή από ακραία κλιματολογικά φαινόμενα. Προτείνονται για χρήση σε πετρελαιοκινητήρες οχημάτων και μηχανημάτων εκτός δρόμου (χρωματοουργικών, εξορύξεων κτλ). Τα χαρακτηριστικά του είναι η τέλεια λίπανση και η αντοχή από την φθορά και την οξείδωση, ενώ διατηρεί καθαρά τα μηχανικά μέρη του κινητήρα.

DE:

Spezielles mineralisches Schmiermittel aus hochqualitativen Materialien mit speziell entwickelten Additiven für Lastwagen-Dieselmotoren entwickelt wurden, die schwere Lasten unter harten Bedingungen transportieren.

RU:

Специальное минеральное масло, изготовленное из высококачественных материалов с добавлением специальных присадок и предназначенное для дизельных двигателей грузовиков, которые перевозят тяжелые грузы и работают в предельно-тяжелых условиях.

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although RS200 motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and RS200 motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.



Typical Chemical Characteristics

Characteristics:

Property	Method	Unit	50	40
Specific Gravity 15°C	ASTM D 1298	kg/L	0,89	0,885
Viscosity at 100°C	ASTM D 445	cSt	16,3 – 21,9	12,5 – 16,3
Viscosity Index	-	-	>110	>110
Pour Point	ASTM D 97	°C	<-15	<-15
Flash Point	ASTM D 92	°C	>210	>210
Total Base Number	ASTM D 2896	mgKOH/g	12,5	12,5
Color	-	-	Crystal gold	Crystal gold

Specifications:

API: CF-4/CF/SJ

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although RS200 motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and RS200 motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.