



TCC (Typical Chemical Characteristics)

TURBO S ISO 32 / 46 / 68 / 100

Description:

EN:
Special enforced lubricant for air, water and steam turbine machines. It has the ability to disaggregate frayed water and also it does not foam.

EL:
Ειδικής ενίσχυσης λιπαντικό για στροβιλιστές αέρος, νερού και ατμού. Έχει την ιδιότητα να διαχωρίζεται από το νερό και να μην προκαλεί αφρισμό.

DE:
Speziell verstärktes Schmiermittel für Luft-, Wasser- & Dampfturbinen. Zersetzt Abwasser ohne Schaumbildung.

FR:
Lubrifiant spécial pour machines à turbines à air, à l'eau et à vapeur. Capable de désagréger l'eau et aussi il ne mousse pas.

RU:
Специальная смазка с улучшенными характеристиками для оборудования с пневматическими, водяными и паровыми турбинами. Обладает способностью дезагрегации отработавшей воды и защитой от вспенивания.

SR:
Specijalno ojacano mazivo za vazdušne, vodene i parne turbine. Posедуje otpornost na vlagu i takotte ne penuša.

BG:
Подсилено масло за въздушни, водни и парни турбини. Отлични противопенни свойства.

RS Laboratory: 15.02.2023

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece [EU] - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



TCC (Typical Chemical Characteristics)

TURBO S ISO 32 / 46 / 68 / 100

Characteristics:

Property	Method	Unit	S-32	S-46	S-68	S-100
Code	-	-	RITUR032	RITUR046	RITUR068	RITUR100
Specific Gravity 15°C	ASTM D 1298	kg/L	0,87	0,875	0,88	0,885
Viscosity at 40°C	ASTM D 445	cSt	28,8 - 35,2	41,4 - 50,6	61,2 - 74,8	90 - 110
Viscosity Index	-	-	>100	>100	>100	>100
Pour Point	ASTM D 97	°C	<-10	<-10	<-10	<-10
Flash Point	ASTM D 92	°C	>200	>200	>200	>200
Color	-	-	Crystal gold	Crystal gold	Crystal gold	Crystal gold

Specifications:

ISO 100:

DIN 51515, Part I, Siemens TLV 9013 04/01
British Standards BS 489, GEGB Standards 207001
General Electric GEK 32568 A/C, MIL-L-17672 D
Brown Boveri HTGD 901 17, US Steel 120
Westinghouse Electric Corp. Turbine Oil Spec.

18L	204L
160460187	160460247

ISO 68:

DIN 51515, Part I, Siemens TLV 9013 04/01
British Standards BS 489, GEGB Standards 207001
General Electric GEK 32568 A/C, MIL-L-17672 D
Brown Boveri HTGD 901 17, US Steel 120
Westinghouse Electric Corp. Turbine Oil Spec.

18L	204L
160460187	160460247

ISO 46:

DIN 51515, Part I, Siemens TLV 9013 04/01
British Standards BS 489, GEGB Standards 207001
General Electric GEK 32568 A/C, MIL-L-17672 D
Brown Boveri HTGD 901 17, US Steel 120
Westinghouse Electric Corp. Turbine Oil Spec.

18L	204L
160460187	160460247

RS Laboratory: 15.02.2023

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



TCC (Typical Chemical Characteristics)

TURBO S ISO 32 / 46 / 68 / 100

ISO 32:

DIN 51515, Part I, Siemens TLV 9013 04/01
British Standards BS 489, GEGB Standards 207001
General Electric GEK 32568 A/C, MIL-L-17672 D
Brown Boveri HTGD 901 17, US Steel 120
Westinghouse Electric Corp. Turbine Oil Spec.

18L	204L
160460187	160460247

Package:

1x18L Pail / 1x204L Drum



RS Laboratory: 15.02.2023

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece [EU] - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.