



Typical Chemical Characteristics

Product:

Anax 4000 “Full SAPS & Fully Synthetic” SAE 10W-60, 5W-50 & 5W-40

Description:

EN:
Fully synthetic engine oil with Full SAPS technology, which is recommended for perfect lubrication on mechanical exhaustion of modified racing engines (rally or tuning), but also for conventional gasoline or diesel engines of European, Japanese, Korean and American OEM.

EL:
Πλήρες συνθετικό λιπαντικό με τεχνολογία Full SAPS, η οποία ενδείκνυται για να παρέχει τέλεια προστασία σε αντίξοες μηχανικές συνθήκες σε αγωνιστικούς κινητήρες (rally ή tuning), αλλά και για συμβατικούς κινητήρες βενζίνης ή πετρελαίου Ευρωπαϊκών, Ιαπωνικών, Κορεάτικων και Αμερικανικών κατασκευαστών.

DE:
Vollsynthetisches Racing Öl für Autos, die erhöhte Schmierung unter allen Bedingungen erfordern und mechanischer Belastung standhalten müssen. Speziell für modifizierte Sport- oder Rennmotoren entwickelt.

RU:
Полностью синтетическое моторное масло для гоночных легковых автомобилей, которым требуются улучшенные характеристики смазывания при любых условиях и стойкости от механического истощения. Специально разработано для модифицированных двигателей спортивных или гоночных автомобилей.

BG:
Състезателно, пълно синтетично моторно масло за автомобили, при които е необходимо продължително смазване при всякакви условия и устойчивост на механично износване. Специално проектирано за доработени двигатели на състезателни или рали автомобили.

FR:
Huile moteur entièrement synthétique pour des applications dans toutes les conditions de course. Spécialement conçu pour les moteurs réglés de voitures de rallye ou course.

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although RS200 motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and RS200 motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.



Typical Chemical Characteristics

Characteristics:

Property	Method	Unit	10W-60	5W-50	5W-40	5W-30	5W-20
Specific Gravity 15°C	ASTM D 1298	kg/L	0,878	0,881	0,879	0,879	0,879
Viscosity at 100°C	ASTM D 445	cSt	21,9 - 26,1	16,3 - 21,9	12,5 - 16,3	9,3 - 12,5	6,9 - 9,3
Viscosity Index	-	-	>130	>130	>130	>130	>130
Pour Point	ASTM D 97	°C	<-25	<-30	<-30	<-30	<-35
Flash Point	ASTM D 92	°C	>210	>210	>210	>200	>200
Total Base Number	ASTM D 2896	mgKOH/g	>6,5	>6,5	>6,5	>6,5	>6,5
Color	-	-	Crystal gold	Crystal gold	Crystal gold	Crystal gold	Crystal gold
Cold Cranking Simulator	ASTM D 5293	mPa-s	<7000 @ 25°C	<6600 @ 30°C	<6600 @ 30°C	<6600 @ 30°C	<6600 @ 30°C

Specifications:

10W-60 & 5W-50:

ACEA: A3/B3-12 & A3/B4-12,
API: SN/SM/SL/CF & Mercedes Benz p229.1

5W-40:

ACEA: A3/B3-12 & A3/B4-12,
API: SN/SM/SL/CF &
VW 502.00 & 505.00

5W-30:

ACEA: A1/B1-12 & A5/B5-12,
API: SN/CF

5W-20:

ACEA: A1/B1-12,
API: SN-RC & ILSAC GF-5,
Ford WSS-M2C948-A/ WSS-M2C948-B
& JLR STJLR.O3.5004

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although RS200 motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and RS200 motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.